

CS180 Exam 2

Xiang Chen

TOTAL POINTS

19.5 / 22

QUESTION 1

7 pts

1.1 Kruskal's algorithm 1 / 1

- 0 Correct algorithm

1.2 Cut property 1 / 1

- 0 Property stated correctly

1.3 MST change when squaring weights 1 / 1

- 0 Correct answer

1.4 WIS: value-to-finish time 2 / 2

- 0 Correct answer, with a valid example showing why the greedy algorithm won't work

1.5 Greedy for same value knapsack 2 / 2

- 0 Correct algorithm, that sorts the items by weight, and fills up the knapsack

mistakes in memoization.

QUESTION 2

2 Proof of cycle property 3 / 3

- 0 Correct proof.

QUESTION 3

3 Knapsack with 3 copies 4 / 4

- 0 Correct algorithm

QUESTION 4

4 Most valuable subsequence 2.75 / 4

- 1.25 Incomplete code but correct logic or single error which clearly affects the final solution while the form of the recurrence is structurally related to correct solution

QUESTION 5

5 RNA with squared norm stability 2.75 / 4

- 1.25 Incomplete unclear code or some mistakes in subproblems or slightly unclear loop formulation or structurally correct recurrence with mistakes or

Mid-term. February 24, 2017

CS180: Algorithms and Complexity
Winter 2017

Guidelines:

- The exam is closed book and closed notes. Do not open the exam until instructed to do so.
- Write your solutions clearly and when asked to do so, provide complete proofs.
- Unless told otherwise you may use results and algorithms we proved in class without proofs or complete details as long as you state what you are using.
- I recommend taking a quick look at all the questions first and then deciding what order to tackle to them in. Even if you don't solve the problems fully, attempts that show some understanding of the questions and relevant topics will get reasonable partial credit.
- You can use extra sheets for scratch work, but try to use the white space (it should be more than enough) on the exam sheets for your final solutions.
- Most importantly, make sure you adhere to the policies for academic honesty set out on the course webpage. The policies will be enforced strictly and any cheating reported.

Problem	Points	Maximum
1		7
2		3
3		4
4		4
5		4
Total		22

Name	Allan (Xiang) Chen
UID	704624388
Section	1B

1 Problem

The answers to the following should fit in the white space below the question.

1. Write down Kruskal's algorithm. It is sufficient to write down the main while loop and the rule describing how the algorithm proceeds. [1 point]

$R = E, T = \emptyset$
 while R is not empty:
 if adding the edge e of smallest weight in R to T doesn't create a cycle:
 add the edge of smallest weight e to T .
 remove e from R


2. State the *cut property* we used in class to analyze Kruskal's and Prim's algorithms. [1 point]

Cut property: assuming all edge weights in a graph G are distinct, let S be a cut of G , let e be the edge of minimal weight crossing the cut. Then e is part of the MST of G .

3. Suppose we are given an instance of the Minimum Spanning Tree Problem on a graph G , with edge costs that are all positive and distinct. Let T be a minimum spanning tree for this instance. Now suppose we replace each edge cost c_e by its square, c_e^2 , thereby creating a new instance of the problem with the same graph but different costs.

True or false: T must still be a minimum spanning tree for this new instance. [1 point]

True



4. Consider the weighted interval scheduling problem where we are given n jobs as input with the i 'th job having start time s_i , finish time f_i , and value v_i . (Thus, the input to the problem is n triples $(s_1, f_1, v_1), \dots, (s_n, f_n, v_n)$.) Recall that our goal is to find the set of non-conflicting jobs with the highest possible total value. Consider the following greedy algorithm for the question:

- (a) Set $A = \emptyset$, $R = \{1, 2, \dots, n\}$.
- (b) While $R \neq \emptyset$:
 - i. Pick job $i \in R$ with highest v_i/f_i (value to finish time ratio) and add i to A .
 - ii. Remove i and all jobs that conflict with i from R .
- (c) Return A .

True or false: A achieves the highest possible total value. If true, provide a brief explanation.

If false, provide a counterexample. [2 points]

False let the input jobs be $(1, 3, 15)$ $(1, 5, 20)$ $(6, 10, 9)$
 $v_i/f_i = 5$ $v_i/f_i = 4$ $v_i/f_i = \frac{9}{10}$

Then the algorithm picks $(1, 3, 15), (6, 10, 9)$
 with total value $15+9=24$, but the
 optimal jobs are $(1, 5, 20)$ and $(6, 10, 9)$
 with total value 29.

5. You have n items with the i 'th item having weight w_i . You also have a knapsack with total weight capacity W (i.e., it can safely hold items whose total weight is at most W). Describe an algorithm for picking a largest possible subset of items that can be placed safely in the knapsack. That is, describe an algorithm to find a subset $S \subseteq \{1, 2, \dots, n\}$ of maximum possible size such that $\sum_{i \in S} w_i \leq W$. For full-credit, your algorithm should run in time $O(n \log n)$. You don't have to prove correctness or analyze the time complexity of the algorithm. [2 points]

[Hint: One approach is to give a greedy algorithm.]

current weight = 0
 $S = \emptyset$
 $R =$ set of all items, sorted in increasing order
 while $R \neq \emptyset$
 let i be the item of the smallest weight in R
 if $w_i + \text{current weight} > W$
 break;
 add i to S
 current weight = current weight + w_i
 return S .

2 Problem



Suppose you have a weighted undirected graph $G = (V, E)$ where all the weights are distinct. Prove that if an edge e is part of a cycle C and has weight more than every other edge in the cycle, then e cannot be part of the minimum spanning tree in G . [3 points]

[Hint: Assume that the statement is false for the sake of contradiction and let T being a MST that contains the edge e . Arrive at a contradiction by a swapping argument as we did in class for proving the cut property.]

Suppose that the statement is false for the sake of contradiction and let T be a MST that contains the edge e . Then since T is a spanning tree, there must be an edge f in the cycle C that is not in T (because otherwise T would have a cycle). Since e has more weight than any other edge in C , then $\text{weight}(f) < \text{weight}(e)$. So if we remove e from T and add f to get a new graph T^* , then total weight of $T^* < \text{total weight of } T$ (since we only replaced one edge with a lighter edge).

So T^* is a MST with lower weight than T , which means T cannot be a MST of G , so a MST of G cannot contain e .

3 Problem

Give a dynamic programming algorithm for the following version of knapsack where you have three copies of each item. There are n types of items with weights w_1, \dots, w_n respectively and value v_1, \dots, v_n respectively and you have **three** copies of each item. Suppose you have a knapsack of total weight capacity W . We say configuration (a_1, \dots, a_n) is *safe* if $0 \leq a_i \leq 3$ and $a_1w_1 + a_2w_2 + \dots + a_nw_n \leq W$ (i.e., it is safe to pack a_1 copies of item 1, a_2 copies of item 2, \dots , a_n copies of item n into the knapsack). The value of a configuration is the total value of the items in the configuration: for a configuration (a_1, \dots, a_n) , its value is $v_1a_1 + v_2a_2 + \dots + v_na_n$.

Give an algorithm which given the numbers $w_1, \dots, w_n, v_1, \dots, v_n, W$ as input computes the maximum value achievable over all safe configurations. For full-credit it is sufficient to give a correct algorithm for the problem which runs in time $O(nW)$ and it is not required to prove correctness or analyze the time-complexity of the algorithm. You must provide full description of the algorithm. [4 points]

$optValue(w_1, \dots, w_n, v_1, \dots, v_n, W):$

$$T(i, w) \equiv \max \begin{cases} T(i-1, w) \\ k \cdot v_i + T(i-1, w - k \cdot w_i) \end{cases}$$
 for $k=1, 2, 3$.

$M = a (n+1) \times (W+1)$ 2-dimensional array
 $M[0][j] = 0$ for all $0 \leq j \leq W$
 $M[i][0] = 0$ for all $0 \leq i \leq n$

for $i = 1, 2, \dots, n$:
 for $j = 1, 2, \dots, W$:
 if $w_i > j$:
 $M[i][j] = M[i-1][j]$.
 else:
 $M[i][j] = \max \begin{cases} M[i-1][j] \\ v_i + M[i-1, j - w_i] \\ \text{if } (2 \times w_i \leq j): 2 \times v_i + M[i-1, j - 2 \times w_i] \\ \text{if } (3 \times w_i \leq j): 3 \times v_i + M[i-1, j - 3 \times w_i] \end{cases}$

return $M[n][W]$.

4 Problem

You are given two arrays of integers $X = [x[0], x[1], \dots, x[m]]$ and $Y = [y[0], y[1], \dots, y[n]]$ as input. For two subsequences of X, Y of the same length, i.e., sequences of indices $0 \leq i_1 < i_2 < \dots < i_k \leq m$ and $0 \leq j_1 < j_2 < \dots < j_k \leq n$, the value of the subsequences is defined as

$$\sum_{\ell=1}^k \frac{1}{1 + |x[i_\ell] - y[j_\ell]|}$$

Give an algorithm that given X, Y as input computes the maximum possible value achievable over all subsequences. For full-credit, your algorithm should run in time $O(mn)$ (ignoring the cost of arithmetic, i.e., adding numbers). You don't have to prove correctness or analyze the time-complexity of the algorithm. [4 points]

Example: $X = [1, 4, 2, 5], Y = [1, 2, 10, 4, 100]$. Here, if you look at subsequences $x[0], x[2], x[3]$ and $y[0], y[1], y[3]$ you get value $1/1 + 1/1 + 1/2 = 2.5$. Whereas, if look at subsequences $x[0], x[1], x[2], x[3]$ and $y[0], y[1], y[2], y[3]$, you get value $1/1 + 1/3 + 1/9 + 1/2 \sim 1.9444$. So the first subsequence has better value. Your goal is to find the best possible value achievable over all subsequences.

[Hint: Create subproblems like we did for edit-distance in class and develop the appropriate recurrence.]

$\text{maxValue}(X, Y):$

$M = \text{a } (m+1) \times (n+1) \text{ 2D array.}$

$M[0][j] = \frac{1}{1 + |x[0] - y[j]|}$ for all $0 \leq j \leq n$

$M[i][0] = \frac{1}{1 + |x[i] - y[0]|}$ for all $0 \leq i \leq m$

for $i = 1, 2, 3, \dots, m:$

for $j = 1, 2, 3, \dots, n:$

$$M[i][j] = \max \left\{ \begin{array}{l} \frac{1}{1 + |x[i] - y[j]|} + M[i-1][j-1] \\ \frac{1}{1 + |x[i-1] - y[j]|} + M[i-2][j-1] \\ \frac{1}{1 + |x[i] - y[j-1]|} + M[i-1][j-2] \end{array} \right.$$

Assume
 $M[0][0] = 0$
 if either
 a or b is
 negative.

return $M[m][n]$

x_1, x_2, \dots, x_n

5 Problem

Consider the following variant of the RNA sequencing question. Given a sequence $X = (x_1, \dots, x_n)$, a set of pairs $M = \{(i_1, j_1), (i_2, j_2), \dots, (i_m, j_m)\}$ is an *allowed* set of pairs if the following hold:

1. Each index appears in at most one pair in M (i.e., no repetitions).
2. Each pair is one of $\{G, C\}$ or $\{A, U\}$. That is, for all $1 \leq p \leq m$, $\{x_{i_p}, x_{j_p}\}$ is one of $\{G, C\}$ or $\{A, U\}$.
3. No sharp edges: For all pairs $(i, j) \in M$, $i < j - 4$.
4. No crossing edges: If pairs $(i, j), (k, \ell) \in M$, then we cannot have $i < k < j < \ell$.

(These are the same rules as we worked with in class.)

The *stability* of an allowed set of pairs M is given by the following formula:

$$\text{stability}(M) = \sum_{p=1}^m (j_p - i_p)^2.$$

That is, the stability of the collection of pairs is the sum of squares of the number of characters between each pair. Give an efficient algorithm that given a sequence $X = (x_1, \dots, x_n)$ computes the maximum possible $\text{stability}(M)$ over all feasible sets of pairs M . For full-credit, your algorithm should run in $O(n^3)$ time. You do not have to prove correctness or analyze the time complexity of the algorithm. [4 points]

stability($X = x_1, x_2, \dots, x_n$):
 return helper(1, n);

$M =$ a global $(n \times n)$ array, initialized to NULL.

helper(i, j):

if $M[i][j] \neq \text{NULL}$
 return $M[i][j]$

if $j \geq i + 4$:

$M[i][j] = 0$

return $M[i][j]$.

max = helper($i, j-1$);

for $k = i+1, \dots, j-1$:

if (i, k) is an allowed pair:

ret = $(j-i+k)^2 + \text{helper}(i, i+k-1) + \text{helper}(i+k+1, j-1)$.

if ret > max:

max = ret

$M[i][j] = \text{max}$

return $M[i][j]$.

